


McAfee Web Gateway



	WW500E	WW1100E	WG-5000	WG-5500
Form Factor	1U rack mount	1U rack mount	1U rack mount	2U rack mount
Processor	Single	Dual Core	Quad Core	2 Quad Core
Memory	2 GB	2 GB	6 GB	12 GB
Interfaces	2 x 10/100/1000	4 x 10/100/1000	4 x 10/100/1000	4 x 10/100/1000
RAID	N/A	Raid 1	Raid 1	Raid 10
Hard Disk	160 GB SATA	2 x 146GB SAS	2 x 300 GB SAS	6 x 300 GB SAS
Power Supply	Single	Single	Redundant	Redundant
Details				
CPU	Intel® Celeron® 440	Intel® Core2Duo E4500	Intel Xeon E5540	Intel® Xeon® E5560
CPU Speed	2.0 Ghz	2.2 Ghz	2.53 Ghz	2 x 2.8 Ghz
CPU Cache (per CPU)	512 KB	2 x 2 MB	8 MB	8 MB
FSB Speed	800 Mhz	800 Mhz	1066Mhz	1333Mhz
Memory	2GB	2GB	6GB	12GB
Memory Speed	667Mhz	667Mhz	1066Mhz	1333Mhz
CD Drive	N/A	24X IDE CD-ROM	DVD-ROM SATA	DVD-ROM SATA
Power Supply	Single 345 W	Single 345 W	Two 717W (hot swappable)	Two 870W (hot swappable)
Voltage	auto switch 110/220V	auto switch 110/220V	auto switch 110/220V	auto switch 110/220V
Max. Amperage	.62 Amps @ 208 Volts	.67 Amps @ 208 Volts	1.7 Amps @ 110 Volts	3.3 Amps @ 110 Volts
Power consumption	129.5 Watts @ 208 Volts	140.1 Watts @ 208 Volts	182.3 Watts @ 110 Volts	355.6 Watts @ 110 Volts
Heat Dissipation	760 BTU/hr	1194 BTU/hr	2446.5 BTU/hr max.	2968.6 BTU/hr max.
Hard Disk	160GB, SATA, 3.5 in. 7.2 RPM	2 x 146GB, SAS 3.5 in. 7.2 RPM	2 x 300GB, SAS, 3.5 in. 10K RPM	6 x 300GB SAS 10K RPM
RAID Controller	—	SAS5iR SAS RAID Controller, Internal, PCIe"	PERC 6/i Integrated Controller Card	PERC 6/i Integrated Controller Card
Remote Management	None	None	iDRAC6 Enterprise	iDRAC6 Enterprise
Chassis				
Dimensions	Height: 1.68" (4.27 cm)	Height: 1.68" (4.27 cm)	Height: 1.67" (4.26 cm)	Height: 3.4" (8.64cm)
	Width: 17.60" (44.70 cm)	Width: 17.60" (44.70 cm)	Width: 18.99" (48.24 cm)	Width: 17.5" (44.31cm)
	Depth: 21.50" (54.61 cm)	Depth: 21.50" (54.61 cm)	Depth: 30.39" (77.2 cm)	Depth: 26.80" (68.07cm)
Weight	~26 lbs (11,8kg)	~26 lbs (11,8kg)	~39 lbs (17.69 kg)	~57.54 lbs (26.1kg)
Environmental				
Operating Temperature	10° to 35° C (50° to 95° F)			
Storage Temperature	-40° C to 65° C (-40° F to 149° F)			
Operating Relative Humidity	20% to 80% (noncondensing)			
Maximum Humidity Gradient	10% per hour, operational and non-operational conditions			
Storage Relative Humidity	Storage Relative Humidity: 5% to 95% (noncondensing)			
Operating Vibration	Max 0.25 G's 0-Peak, 3-200 HZ sweep @ 1/2 Octaves/min	0.26 Grms at 5Hz to 350Hz in operational orientations		
Storage Vibration	Max 1.54 GRMS - 6 sides@15 min/side	1.54 GRMS random vibration at 10Hz to 250Hz in all orientations		
Operating Shock	Operating Max Shock: 31G, 2.6ms, 20in/sec, bottom side		Half sine shock in all operational orientations of 31G +/- 5% with a pulse durations of 2.6 ms +/-10%	
Storage Shock	Max 71G, 2ms, 35in/sec, 6 sides; 32G, 2ms, 270in/sec, 6 sides		Half sine shock on all six sides of 71G ±5% with a pulse duration of 2 ms ±10%; Square wave shock on all six sides of 27G with velocity change @235 in/sec or greater	
Operating Altitude	-16 to 3,048m (-50 ft to 10,000 ft)			
Storage Altitude	-16m to 10,600m (-50 ft to 35,000 ft)			
Safety Standards				
EN60950-1, First Edition: Standard for Information Technology Equipment—Safety-Part 1: General Requirements				
IEC 60950-1, First Edition (2001)				
UL/CSA 60950-1, First Edition: Standard for Information Technology Equipment—Safety-Part 1: General Requirements				
				
EK1-ITB 2000:2003 : Ergonomics				
ISO 9241 : VDT Ergonomic Requirements				
ZH1/618:GS-VW-SG7:1997 :Ergonomics				
ISO 13406-2 : Ergonomic requirements for work with visual displays based on flat panels				
ISO 7779 : Sound Pressure at Operator Position (Acoustics)				
MsanPIN 001-96: Interstate Sanitary rules and norms (Acoustics)				
Management				
Web Management	Yes			
Secure Command Line Interface	Yes			
Reporting via	McAfee Web Reporter			
Multi-language Support (Interface)	N/A			
Multi-language Support (Error messages)	English, French, German, Japanese, Korean, Italian, Chinese, Portuguese, Spanish			
Functionality Available On-Box				
Web Filtering (URL Filter)	Yes			
Anti-Malware	Yes			
Anti-Virus	Yes			
SSL Scanner	Yes			
McAfee Web Reporter	No			
Other Features				
ICAP Protocol Support	Yes			
IFP Protocol Support	Yes			
WCCP support	Yes			